

**PHYSICOCHEMICAL ANALYSIS OF GROUNDWATER SAMPLES OF BICHI LOCAL GOVERNMENT AREA OF KANO STATE OF NIGERIA.****Emmanuel Bernard<sup>1</sup> and Nurudeen Ayeni<sup>2</sup>**

<sup>1</sup>Department of Chemistry, Federal College of Education (Technical) Bichi, Kano – Nigeria.

<sup>2</sup>Department of Chemistry, Federal College of Education , P.M.B 3045, Kano – Nigeria.

**Abstract**

*The physicochemical properties of groundwater from various locations in Bichi Local Government Area of Kano State were analysed. The samples taken from twenty different locations revealed that the study area has a mean of Turbidity 2.0 NTU, Colour 2.5 TCU, Temp. 25°C, P<sup>H</sup> 6.8, Total Alkalinity 85.0 mg/l, Total Hardness 71.83 mg/l, Calcium 25.24 mg/l, Magnesium 2.19mg/l, Iron 0.05, Chloride 7.89mg/l, Nitrate 0.79 mg/l, Total dissolved solid 81.0 mg/l, Conductivity 135 µS/cm,. By observing the results, it was shown that the parameters from the water samples were within WHO and SON permissible limit for ground water which satisfy the safety limit for its use for various purposes like domestic, agricultural, industrial and so on.*

**Keyword:** Physicochemical properties, Groundwater, Bichi, Drinking, Water,

**1. Introduction**

Water as a universal solvent has the ability to dissolve many substances be it organic or inorganic compound. With this outstanding property, nevertheless it is almost impossible to have water in its pure form since it cannot be held up in a vacuum. Water which occurs below the water table is referred to as groundwater. In Bichi, groundwater is one of the main sources of water used. Uncensored human activities in developing countries contribute immensely to the poor quality of groundwater. The problems of groundwater quality are much more acute in areas which are densely populated, with localization of industries. Water for human consumption must be free from organisms and chemical substances in concentration large enough to affect health.( Bruvold & Ongerth 1969; APHA, 1995; WSC, 2007; Brian 2007) .

.The addition of various kinds of pollutants through sewage, industrial effluents, agricultural run off etc. into the water main stream brings about a series of changes in the physicochemical characteristics of the water, which have been the subject of several investigations (WHO/UNEP, 1989; Ayodele and Abubakar, 1998). In Northwest Nigeria the pollution of groundwater was traced to shallow water table that intercepts pit latrines

<http://www.ejournalofscience.org>

and soaks away pits. (Oteze, 1993) A number of chemical contaminants have been shown to cause adverse health effects in humans as a consequence of prolonged exposure through drinking-water from various sources. (Bruvold & Ongerth 1969; Oteze, 1993; APHA, 1995)

The objective of this study is to evaluate some of the parameters that can cause contamination and in what concentration if present and comparing it with set standards of World Health Organization and Standard Organization of Nigeria.

## **2. Materials and Methods.**

### **2.1. Description of Study Area**

Bichi Local Government Area is hosted by Kano state which is ranked second in population with about 9.0million people and lies between latitude 11°30' and 11.5°N and longitude 8°30' and 8.5°E and the state is the second largest in Nigeria. Nigeria is located approximately between latitude 4° and 14° North of the equator, and between longitude 2° 2' and 15° east of the Greenwich meridian Wikipedia (2012)

### **2.2. Collection/Treatment of Water Samples.**

Samples were collected from twenty locations of drinking water in plastic containers previously washed with detergents and HNO<sub>3</sub> acid and later rinsed with sampled water several times. 2M HNO<sub>3</sub> was added to samples for metallic ions determination, this is to maintain the stability of the oxidation state of the various elements in solution and prevent precipitation. (NAS, 1986 ; WHO,;2003; SON 2007) .

### **2.3. Physicochemical Analysis.**

#### **Temperature**

The temperatures of the samples were measured at the point of collection using mercury in glass thermometer.

#### **Electrical conductivity and P<sup>H</sup>**

The conductivity of the samples was determined using a Jenway model 4010, and the P<sup>H</sup> Meter, model PBS – 51, EL – Hama instrument was used to determine the P<sup>H</sup> value.

#### **Turbidity**

A turbidimeter model HACH 2100Q Colorado, was used to determine the turbidity of the samples.

#### **Total Alkalinity**

It was determined by titrimetric method using standard solution of 0.01M HCl and methyl orange as indicator.

### **Total Hardness**

It was measured using EDTA (Ethylene – Di amine Tetra – Acetic Acid) as titrant with ammonium chloride and ammonium hydroxide buffer solution and Erichrome Black T as indicator.

### **Chloride content**

It was determined by Mohr's method using silver nitrate as titrant and potassium chromate solution as indicator.

### **Total Dissolved Solid**

This was determined by evaporation method in an oven maintained at 200°C for 2hrs.

### **Calcium Hardness**

Calcium hardness was determined using EDTA method with murexide (ammonium purpate) as indicator.

### **The Cationics**

100cm<sup>3</sup> of the water sample was pre-concentration by heating in a vacuum until the sample was reduced to 25cm<sup>3</sup>. Determination was done using the atomic absorption spectrophotometer, Model Alpha 4 for magnesium and iron and flame photometer, model PF7, Jenway for calcium

## **3. Results and Discussion.**

The result of physical and chemical parameters obtained from the analysis of water samples are shown in Table 1.

**Table 1:**Physico-chemical Analysis of Ground Water in Bichi Local Govt. Area of Kano.

Parameters	Range	Mean	SON	WHO
Temp. °C	24.5 - 26.2	25	Ambient	
Color TCU	1.8 - 3.0	2.5	15	15
pH	6.3 - 8.2	6.8	6.5- 8.5	6.5 – 9.5
Conductivity. $\mu$ S/cm,	126 – 143	135	1000	
Turbidity NTU	1.7 -2.4	2.0	5	5
Alkalinity. (Methyl orange) mg/l	74.3 - 88.2	85.0		
Harness.(as CaCO <sub>3</sub> ) mg/l	68.0 – 75.8	71.83	150	500
Calcium. (Ca <sup>+2</sup> ) mg/l	24.2 - 30.3	25.24		100 – 300

<http://www.ejournalofscience.org>

Magnesium. (Mg <sup>+2</sup> ) mg/l	2.00 – 4.67	2.19		
Chloride. mg/l	7.10 – 8.45	7.89	250	250
Iron (Fe <sup>+2</sup> )	0.00 – 0.05	0.05	0.3	0.3
Nitrate. mg/l	0.52 - 1.03	0.79	50	50
TDS. mg/l	79.0 - 86.7	81.0	500	500 – 1000

SON (Standard Organization of Nigeria); WHO (World Health Organization)

The value of temperature in the study area ranged from 24.5 - 26.2 °C. It is noted that high water temperature enhances the growth of microorganisms and may increase taste, odor, color and corrosion problems.

The color ranged from 1.8 - 3.0 TCU which is within WHO and SON permissible limit. Color in drinking-water is usually due to the presence of colored organic matter (primarily humic and fulvic acids) associated with the humus fraction of soil or the presence of iron and other metals, either as natural impurities or as corrosion products. (WHO, 2011)

The P<sup>H</sup> values of samples range is 6.3 - 8.2 which conform to WHO and SON standard for drinking water. Although pH usually has no direct impact on consumers, it is one of the most important operational water quality parameters.

The conductivity concentrations range were 126 – 143  $\mu$ S/cm which were below SON standard for drinking water.

The turbidity value of the study area ranged between 1.7 – 2.4. Turbidity in drinking-water may be due to the presence of inorganic particulate matter in some groundwater or sloughing of biofilm within the distribution system.. High turbidity value can protect microorganisms from the effects of disinfection thereby can stimulate bacterial growth. The value is within WHO and SON standard for drinking water. (SON 2007; WHO, 2011)

The alkalinity of water may be caused by dissolved strong bases such as sodium or potassium hydroxide (and other hydroxide containing compounds), hydroxide ions are always present in water, even if the concentration is extremely small. The alkalinity value ranged between 74.3 - 88.2 mg/l. When water has high alkalinity it is concluded that it is well buffered. It resists a decrease in pH when acidic rain snowmelt, enters it. If water has an alkalinity below about 100mg/L as CaCO<sub>3</sub>, it is poorly buffered and pH sensitive. This could be harmful to the plants and animals that live there. (WSC, 2007; SON 2007; WHO, 2011)

---

<http://www.ejournalofscience.org>

The range of hardness analyzed is 68.0 - 73.8 mg/L and fell below W.H.O and S.O.N standard of drinking water. Hardness caused by calcium and magnesium usually results in excessive soap consumption and subsequent “scum” formation. In some instances, consumers tolerate water hardness in excess of 500 mg/l. Depending on the interaction of other factors, such as pH and alkalinity, water with hardness above approximately 200 mg/l may cause scale deposition in the treatment works, distribution system and pipe work and tanks within buildings. Soft water, with a hardness of less than 100 mg/l, may, have a low buffering capacity and so be more corrosive for water pipes. (WHO,;2003 ; SON 2007; WHO, 2008; WHO, 2011)

The analysis of calcium revealed a range of between 24.2 - 30.3 and the W.H.O standard of drinking water indicates that the taste threshold for the calcium ion is in the range of 100–300 mg/l, depending on the associated anion. Magnesium concentration in samples were in the range of 2.00 - 4.67, both cations are the major cause of hardness in water (WHO,;2003 ; WHO, 2008; WHO, 2011)

Chloride in drinking-water originates from natural sources, sewage and industrial effluents, urban runoff containing de-icing salt and saline intrusion. No health-based guideline value is proposed for chloride in drinking-water by WHO and SON standard of drinking water. However, chloride concentrations in excess of about 250 mg/l can give rise to detectable taste in water and the observed range is 7.10 - 8.45 mg/l (SON , 2007; WHO, 2008;WHO, 2011)

Nitrate can reach both surface water and groundwater as a consequence of agricultural activity (including excess application of inorganic nitrogenous fertilizers and manures), but groundwater concentrations generally show relatively slow changes. Some ground waters may also have nitrate contamination as a consequence of leaching from natural vegetation. The concentration range of 0.52 - 1.03 mg/l was observed which was below the WHO and SON standard of drinking water permissible limit. SON., 2007; WHO,;2003; WHO, 2011)

Iron concentrations range was 0.00 – 0.05 mg/l. It is noted that anaerobic groundwater may contain ferrous iron at concentrations of up to several mg/l without discoloration or turbidity in the water when directly pumped from a well. On exposure to the atmosphere, however, the ferrous iron oxidizes to ferric iron, giving an objectionable reddish-brown color to the water. Iron also promotes the growth of “iron bacteria,” which derive their energy from the oxidation of ferrous iron to ferric iron and in the process deposit a slimy coating on the piping (SON, 2007; WHO, 2011)

TDS values were in the range of 79.0 - 86.7mg/l, it comprises inorganic salts (principally calcium, magnesium, potassium, sodium, bicarbonates, chlorides and sulfates) and small amounts of organic matter that are dissolved in water. TDS in drinking-water originate from natural sources, sewage, urban runoff and industrial wastewater. Concentrations of

---

<http://www.ejournalofscience.org>

TDS in water vary considerably in different geological regions owing to differences in the solubility of minerals. The palatability of water with a TDS level of less than 600 mg/l is generally considered to be good; drinking-water becomes significantly and increasingly unpalatable at TDS levels greater than about 1000 mg/l. The presence of high levels of TDS may also be objectionable to consumers, owing to excessive scaling in water pipe, heaters, boilers and household appliances. No health-based guideline value for TDS has been proposed. Water with extremely low concentrations of TDS may also be unacceptable because of its flat, insipid taste. <sup>[3][11][12][13]</sup>

Bichi Local Government Area though not absolutely an urban and industrial area have a relatively high TDS concentration, which is an evidence that there are soluble mineral salts in the geographical region.

#### 4. Conclusions

Informing the public of the state of their drinking water should be considered as an important aspect of social responsibility as well as scientific research. Consumers may be aware of a potential problem with the safety of drinking water because of media coverage or access to research work. Lack of confidence in the drinking-water or the authorities may drive consumers to alternative, potentially less safe sources. Not only do consumers have a right to information on the safety of their drinking-water, but they have an important role to play in assisting the authorities by their own actions and by carrying out the necessary measures at the individual level. Safe drinking water is vital to sustain life and a satisfactory (adequate, safe and accessible) supply must be available to all. Improving access to safe drinking-water can result in tangible benefits to health. Every effort should be made to achieve drinking-water quality as safe as practicable.

The results obtained from the analysis of the samples revealed that the quality of ground water in Bichi been assessed by comparing each concentration with the standard desirable limit of that parameter in drinking water as prescribed by WHO and SON, are within permissible limits.

#### REFERENCES

- Ayodele, J. T and Abubakar, M. B, (1998). Trace Elements Contamination of Rainwater in the Semi arid Region of Kano. Nigeria. *Journal of Environmental Management and Health*, vol. 9, No. 4.
- Brian O. (2007) Environmental Quality Centre Environmental Engineering and Earth Sciences Wilkes University. Wilkes- Barre, PA 1876. Webmaster.
- Bruvold WH, Ongerth HJ: (1969) "Taste Quality of Mineralized Water". *Journal of The American Water works Association* Vol. 61:170.
- National Academy of Science. (1986) Eutrophication causes consequences and correctives. *Nat. Acad. Sci. Washington, D.C.*
- Oteze, G. F (1993) Tropical soil in Nigeria in Engineering, Groundwater level and groundwater Management. Balkema Rotterdam, Netherland p. 172.
- Standard Method for the Examination of Water and Wastewater, (1995). American Public Health Association (APHA), American Water Works Association (AWWA), Water Environment Federation, (WEF). 19<sup>th</sup> Edition
- Standards Organisation Of Nigeria (2007) Nigerian Standard for Drinking Water Quality Abuja, Nigeria.
- Water System Council (2007) "Wellcare Publications" Retrieved from [www.wellcarehotline.org](http://www.wellcarehotline.org).

---

<http://www.ejournalofscience.org>

Wikipedia (2012) Kano State of Nigeria, Wikimedia Foundation, Inc., Retrieved from [http://en.wikipedia.org/w/index.php?title=Kano\\_State&oldid=458252590](http://en.wikipedia.org/w/index.php?title=Kano_State&oldid=458252590)

WHO/UNEP, (1989), GEMS. Global Freshwater Quality. Oxford, Alden Press.

World Health Organisation, (2003) “Guidelines For Drinking Water Quality, Health Criteria and Other Supporting Information 2<sup>nd</sup> Edition Vol. 2.

World Health Organisation, (2008) Guidelines for Drinking-water Quality Incorporating the First and Second Addenda Volume 1 Recommendations, 3<sup>rd</sup> Edition, Geneva.

World Health Organisation, (2011) Drinking Water Standards and Health Advisories Office of Water U.S. Environmental Protection Agency Washington, DC.